

ABAS Protect's product standard prescribes different levels of security for industrial gates. The product standard for industrial gates in security level 1 is defined below.

## Industrial gates

<b>Standard height:</b>	1950 mm plus optional barbed wire
<b>Standard width:</b>	1000–5000 mm in intervals of 500 mm
<b>Material:</b>	Front/back stem 60x60x1.5 mm on frame < 4.0 m Front/back stem 60x60x2.0 mm on frame > 4.5m Top/bottom beam 60x60x1.5 mm on frame < 3.0m Top/bottom beam 60x60x2.0 mm on frame 3.5 m och 4.0 m Top/bottom beam 60x60x3.0 mm on frame > 4.5m Standing profiles in frame 25x25x1.25 mm
<b>Implementation:</b>	Hot-dip galvanized according to UNI-EN ISO 1461 (mean thicknes 55µm) Powder coated (ca. 80–100 µm)
<b>Assembly details:</b>	Plastic caps, ground pins, hinges, padlock loop

## Posts

<b>Posts:</b>	Manufactured for casting or with welded base plate (length 2340 mm) Standard length 3000 mm in dimensions: 80x80x2.0 mm (walk gate) 100x100x2.0 mm 120x120x4.0 mm 150x150x5.0 mm
<b>Implementation:</b>	Hot-dip galvanized according to UNI-EN ISO 1461 (mean thicknes 55µm) Powder coated (ca. 80–100 µm)
<b>Assembly details:</b>	Plastic caps, tension rod, staples, rivets, tension screws and brace screws

Warranty: 2 years in general for ABAS products.