

ABAS Protect's product standard prescribes different levels of security for fence and gates. The product standard for industrial fence in security level 2 is defined below.

## ProNet

<b>Height:</b>	Standard heights 1230, 2030, 2430 mm
<b>Wire diameter:</b>	Two standard alternatives: Vertical wire 6.0 mm, horizontal wires 2 x 8.0 mm (8/6/8) Vertical wire 6.0 mm, horizontal wires 2 x 5.0 mm (5/6/5)
<b>Mesh size:</b>	Three standard sizes: 200 x 50mm 200 x 25mm 50 x 50mm
<b>Implementation:</b>	Welded three wire panel fence, our label: ProNet Sections in width ca. 2500 mm Hot-dip galvanized according to UNI-EN ISO 1461 (mean thickness 55µm) Powder coated (ca. 80–100 µm)

## Posts

<b>Post height:</b>	Corresponding to panel height plus part for embedding (ca. 400 mm)
<b>Modell variants:</b>	Line, corner and end posts (L/C/E)
<b>Tube profiles:</b>	60x40x2.0 mm (standard) 70x50x3.0 mm (alternative)
<b>Implementation:</b>	Hot-dip galvanized (UNI-EN ISO 1461) Pre-galvanized (UNI-EN 10346, 25–30 µm) + powder coating (ca. 80–100 µm)

Warranty: 2 years in general for ABAS products.